

**METHOD AND INSTRUMENT FOR ESTABLISHING THE RECEIVING SITE OF A CORONARY ARTERY BYPASS GRAFT**

Patent Number: WO9517127  
Publication date: 1995-06-29✓  
Inventor(s): RYGAARD JOERGEN A (DK)  
Applicant(s): RYGAARD JOERGEN A (DK); OTICON AS (DK)  
Requested Patent: ☐ WO9517127  
Application Number: WO1994DK00148 19940412  
Priority Number(s): DK19930001455 19931223  
IPC Classification: A61B17/11 ; A61B17/32  
EC Classification: A61B17/11, A61B17/32E  
Equivalents: CA2179507, CA2179508, DE69419437D, DE69419437T, DE69419780D, DE69419780T, ☐ DK145593, ☐ EP0740531, ☐ EP0774923, ES2137366T, ES2138081T, JP2997315B2, JP2997316B2, JP9503420T, KR189276, KR189277, ☐ WO9517128

**Abstract**

In a method for locating an arterial constriction and performing an arteriotomy distally thereof, especially with a view to establishing a bypass connection between the aorta (52) and a part of the coronary artery (51) distally of a constriction in the artery, the most important steps are: (a) locating the site of the constriction in the artery (51), preferably by using an instrument (9) with a head (3) carrying an ultrasonic transducer array (not shown), and (b) making an incision in the artery (51) closely distally of the constriction, preferably by using a knife (not shown) placed in said head (3). By proceeding in this manner, it is possible to perform the initial steps of a coronary bypass operation swiftly and accurately on a beating heart.

Data supplied from the esp@cenet database - I2

BEST AVAILABLE COPY